Product leaflet

ProductModel No.Ordering No.Compressed Air-fed MaskSR 90 Airline M/L, SilikonH03-1512SR 90 Airline S/M, SilikonH03-1612

Product Description

SR 90 Airline is a compressed air mask with filter back-up, designed for connection to an appropriate compressed air supply with breathable air. The overpressure which builds up in the mask prevents contaminated ambient air from reaching the user. SR 90 Airline can be used as an alternative to filter protection in all situations where such protection is recommended. This applies particularly to heavy work or long-duration work, and where contaminants do not provide adequate warning, or are especially toxic.

The mask is made from a material that does not cause sparks in the event of friction, which allows it to be used in explosive or inflammable environments.

The control valve is fitted with a warning whistle which operates if the air quantity falls below the recommended value. A flow meter for monitoring air flow is included. Compressed air should be purified with a Sundströms SR 99-1 compressed air filter. See separate production information.

Technical specification

	SR 90 Airline	EN 14594:2005
Working pressure	4-7 bar	≤ 10 bar
Airflow rate	150-320 l/min	150-320 l/min
Service temperature	-10 – +55°C, < 90% RH	-
Storage temperature	-20 – +40°C, < 90 % RH	-
Weight without control valve	≈ 280 g	-
Low flow warning level	< 150 l/min	≤ 150 l/min
Assigned Protection Factor ¹	20 (3A)	-
Nominal Protection Factor ²	200 (3A)	-
Approvals	EN 14594:2005, 3A EN 140:1998	-

¹⁾ Specified in BS EN 529 and applies generally to all approved continuous flow airline half masks regardless of the test results.

- 2) According to EN 529:2005.
- A. Half mask
- B. Breathing hose
- C. Retaining clip
- D. Belt
- E. Control valve
- F. Warning whistle
- G. Compressed air supply hose
- H. Flow meter
- I. Filter combination
- J. Sealing cover



www.srsafety.com



